F-rack

ACCESSORIES FOR SZE2 CABINETS

19" SWING FRAME



Asymmetrical swing frame with 150 kg load capacity mounted in the SZE2 cabinet

Notes

Cabinet with a swing frame should be fixed to the floor of the room to prevent tipping. On customers request, we make cabinets with swing frames with the possibility of opening by 180°.

DESIGN

- 1. Cabinet frame
- 2.19" swing frame 3. Top supporting bar

- A. Bottom supporting bar
 Bottom supporting bar
 Masking panel for symmetrical frame
 Masking panel for asymmetrical frame



Available in symmetrical and asymmetrical options. Equipped with door-stop.

Two locks with double-bit insert.

Possibility of left- or right-side assembly by 180° rotation.

Maximum opening angle: 120°

Load capacity: 150 kg

Material


Sheet steel and steel profiles powder painted in RAL 7035

Scope of delivery


Swing frame with fixing accessories for mounting to the cabinet.

For cabinet		Usable			
Width [mm]	Height [mm]	height of the frame HU [V = 44.45 mm]	Swing frame type	Maximum depth for installations D _{max} [mm]	Catalogue number
600	2000	40 U	symmetrical	180	WZ-1951-29-05-011
	2200	44 U	symmetrical	180	WZ-1951-29-08-011
800	2000	40 U	symmetrical	360	WZ-1951-29-01-011
			asymmetrical	440	WZ-1951-20-01-011
	2200	44 U	symmetrical	360	WZ-4950-26-00-011
			asymmetrical	440	WZ-4950-27-00-011

Package: 1 pc.




A-A section




Cabinet 800 mm wide

with symmetrical swing frame

Front view without door







C



137





034 ZPAS

19" SWING FRAME

180

INDUSTRIAL ENCLOSURES

F-rack

ACCESSORIES FOR SZE2 CABINETS

19" SWING FRAME

19" swing frame with increased load capacity

On customers request, it is possible to make SZE2 cabinet with a swing frame with a load capacity of 200 kg.

The swing frame then has an overrun wheel and the cabinet's frame has special strengthening which prevents it from deforming during opening the loaded frame.

For detailed information, please contact ZPAS sales department.



Example of SZE2 cabinet with strengthened frame equipped with a swing frame with 200 kg load capacity



F-rack

ACCESSORIES FOR SZE2 CABINETS

MOUNTING PLATE



Mounting plate







Mounting plate

The mounting plate is designed for installing different equipment inside the SZE2 cabinet. Detailed dimensions of the mounting plates are given in the drawing on page 17.

Material

Al-Zn-coated steel sheet, 3 mm thickness; dimensional tolerances sheet steel are normal according to EN 10143.

Scope of delivery

Mounting plate with cabinet fixing accessories. Mounting plate guides are sold separately.

	For cabinet	Catalogue number	
Height [mm]	Width [mm]		
	600	WZ-1951-67-10-000-BP	
2000	800	WZ-1951-67-07-000-BP	
2000	1000	WZ-1951-67-04-000-BP	
	1200	WZ-1951-67-01-000-BP	
	600	WZ-4950-28-10-000-BP	
2200	800	WZ-4950-28-07-000-BP	
2200	1000	WZ-4950-28-04-000-BP	
	1200	WZ-4950-28-01-000-BP	

Package: 1 pc

Note:

On customers request, we make hinged mounting plates, using galvanized steel sheet or textolite plate. The mounting plate can also be powder-painted in RAL 7035 (standard colour) or any other colour on demand.

Mounting plate guides

The guides are designed for installing the mounting plate in the SZE2 cabinet. They make inserting and positioning the plate inside the cabinet easier.

Material

Al-Zn-coated steel sheet

Scope of delivery

Set of 2 guides together with accessories for fixing them on the bottom plate of the cabinet.

For cabinet depth [mm]	Catalogue number
400	WZ-1951-64-04-000
500	WZ-1951-64-03-000
600	WZ-1951-64-02-000
800	WZ-1951-64-01-000

Package: 1 set

Accessories for SZE2 cabinets